



Klima-E flow 150 wall conduct

Product number: 4022040

Configuration: white, stainless steel

Configuration options

4022040 | white, stainless steel

✓ Wall sleeve

✓ installation in the wall

Stainless-steel external blind with backpressure shutter.

With rectangular connector for COMPAIR® flow 150.

— tube connector 227 x 94 mm

— connector depth 80 mm

— installation depth 420–620 mm, can be shortened to 210 mm

— wall penetration Ø about 155 mm



[more infos...](#)

Technical data

Article type	Wall sleeve	Diameter wall opening	155 mm
Material	stainless steel	Connection diameter	150 mm
Properties	can be shortened	Installation depth	420–620 mm
Mounting/Fixing	installation in the wall	Wall box version	stainless steel external blind with backflow trap rectangular connector for COMPAIR® flow 150
Certification	stainless	Pipe socket dimension	pipe connector 227 x 94 mm
Shortenability	can be shortened to 210 mm	System dimension	150
Shape	angular	Output drive	angular
Support depth	80 mm	Ventilation system	COMPAIR flow 150

Pos.	Anzahl	Arzt.	Arzt.	Benennung	Artikel Nr.	Werkstoff
1	1		1	Mauerkasten 150 mm	440345	PP
2	1		1	Flansch 150 mm	440009	PVC
3	1		1	E-Flan 150 mm	440042	Netzschalter Stahl (1.4301)